

# Jira - ScriptRunner Reporter를 Assignee로 설정하기

Jira 이슈를 생성할 때 report와 assignee가 항상 동일한 경우에 유용한 ScriptRunner script를 소개한다.

Assignee field가 설정되지 않으면 report를 assignee에 설정

Behaviour: 4 - Set assignee from reporter

When finished view all [behaviours](#).

**General Settings**

Use Validator Plugin  
This will check your workflow for uses of the Fields Required validator in Jira Suite Utilities, and mark those fields as required.

Guide Workflow  
Use this setting to allow the tool to show you actions and state names when using Conditions.

**Fields**

**Field: Assignee**  
Required

**Optional (Require)**  
**Writable (Readonly)**  
**Shown (Hide)**

Validation Script (edit):  
import com.atlassian.jira.component.ComponentAccessor  
import com.atlassian.jira.groovy.user.FieldsBehaviours  
Edit server-side script | Delete server-side script

Conditions: None - Add one. ⓘ

## ScriptRunner Behaviour Script

```
import com.atlassian.jira.component.ComponentAccessor
import com.onresolve.jira.groovy.user.FieldsBehaviours
import static com.atlassian.jira.issue.IssueFieldConstants.*
import groovy.transform.BaseScript

def assignee = getFieldById(ASSIGNEE)
def reporter = getFieldById(REPORTER)

if (!underlyingIssue?.assignee) {
    assignee.setFormValue(reporter.getValue())
}
```

Name	Mappings	Operations
2 - Start Progress Start Progress (due date field required)	<a href="#">Start Progress (All Issue Types) Delete</a>	<a href="#">Fields   Add Mapping   Edit   Delete Behaviour</a>
3 - In Review In Review (due date field read-only)	<a href="#">Start Progress (All Issue Types) Delete</a>	<a href="#">Fields   Add Mapping   Edit   Delete Behaviour</a>
4 - Set assignee from reporter	<a href="#">ALM Demo (Story) Delete</a>	<a href="#">Fields   Add Mapping   Edit   Delete Behaviour</a>

## 4 - Set assignee from reporter로 추가한 모양

- ALM Demo project의 Story issue type에 적용