

분석 예외 정의 방법

Original site = <https://docs.sonarqube.org/display/SONAR/Analysis+Parameters>

Patterns

Paths are relative to the project base directory.

The following wildcards can be used:

Wildcard	Matches
*	zero or more characters
**	zero or more directories
?	a single character

Relative paths are based on the fully qualified name of the component (like the one displayed in the red frame below):

[blocked URL](#)

Examples

sonar-project.properties

```
# Exclude all classes ending by "Bean"
# Matches org/sonar.api/MyBean.java, org/sonar/util/MyOtherBean.java, org/sonar/util/MyDTO.java, etc.
sonar.exclusions=**/*Bean.java,**/*DTO.java

# Exclude all classes in the "src/main/java/org/sonar" directory
# Matches src/main/java/org/sonar/MyClass.java, src/main/java/org/sonar/MyOtherClass.java
# But does not match src/main/java/org/sonar/util/MyClassUtil.java
sonar.exclusions=src/main/java/org/sonar/*

# Exclude all COBOL programs in the "bank" directory and its sub-directories
# Matches bank/ZTR00021.cbl, bank/data/CBR00354.cbl, bank/data/REM012345.cob
sonar.exclusions=bank/**/*

# Exclude all COBOL programs in the "bank" directory and its sub-directories whose extension is .cbl
# Matches bank/ZTR00021.cbl, bank/data/CBR00354.cbl
sonar.exclusions=bank/**/*.*cbl
```

Sonar for Bamboo

Tasks

A task is a piece of work that is being executed as part of the build. The execution of a script, a shell command, an Ant Task or a Maven goal are only few examples of Tasks. [Learn more about tasks.](#)

You can use [runtime](#), [plan and global variables](#) to parameterize your tasks.

1 agent has the [capabilities](#) to run this job

Source Code Checkout

Checkout Default Repository

Maven 3.x

Sonar Scanner

Final tasks

Are always executed even if a previous task fails

Drag tasks here to make them final

Add task

Sonar Scanner configuration

[Need help in configuring this task?](#)

Task description

☐ Disable this task

NOTICE: project configuration is read from the sonar-project.properties file in your repository.

Build JDK

JDK

Add new JDK

Which JDK do you need to use for the build? the JAVA_HOME will be added as an environment variable.

SonarQube Scanner executable

sonar-scanner

Add new executable

The path to the SonarQube Scanner executable home. You do not need to configure this if you want to use remote agents and have configured the path to your SonarScanner installation with the environment variable "SONAR_SCANNER_HOME" or by configuring "system.builder.sos" in your capabilities file at "BAMBOO_AGENT_HOME/bin/bamboo-capabilities.properties".

Environment variables

e.g. SONAR_SCANNER_OPTS="-Xmx512m". Separate multiple values by space.

Working subdirectory

Specify an alternative subdirectory as a working directory for this task.

Additional parameters

-Dsonar.java.binaries=target;-Dsonar.exclusions=src/test/**/*.java,src/**/*.xml

e.g., "-Dsome.property=some.value -Pcoverage-per-test" or "/d:some.property=some.value" when using MSBuild

Maven POM

pom.xml

```
<properties>
<sonar.exclusions>*/Name*.java</sonar.exclusions>
</properties>
```